



Technické údaje	BS 1600	BS 1800	BS 2100	BS 2400	BS 1800 4V	BS 2100 4V	BS 2400 4V	BH 1800	BH 2100	BH 2400	BH 1800 4V	BH 2100 4V	BH 2400 4V
Pracovní šířka	1,6 m	1,8 m	2,1 m	2,4 m	1,8 m	2,1 m	2,4 m	1,8 m	2,1 m	2,4 m	1,8 m	2,1 m	2,4 m
Počet nožů a přírub	36 / 7	42 / 8	48 / 9	54 / 10	42 / 8	48 / 9	54 / 10	42 / 8	48 / 9	54 / 10	42 / 8	48 / 9	54 / 10
Vstupní rychlost PTO	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm
Rozměry nožů	8x200 mm	8x200 mm	8x200 mm	8x200 mm	8x200 mm	8x200 mm	8x200 mm	8x200 mm	8x200 mm	8x200 mm	8x200 mm	8x200 mm	8x200 mm
Minimální požadavek HP	40-55 hp	55-65 hp	65-75 hp	70-85 hp	55-65 hp	65-75 hp	70-85 hp	55-65 hp	65-75 hp	75-90 hp	55-65 hp	65-75 hp	75-90 hp
Pracovní hloubka	20 cm	20 cm	20 cm	20 cm	20 cm	20 cm	20 cm	20 cm	20 cm	20 cm	20 cm	20 cm	20 cm
Transportní šířka	1,6 m	1,8 m	2,1 m	2,4 m	1,8 m	2,1 m	2,4 m	1,8 m	2,1 m	2,4 m	1,8 m	2,1 m	2,4 m
Hmotnost stroje	415 kg	455 kg	510 kg	565 kg	480 kg	530 kg	575 kg	620 kg	655 kg	680 kg	630 kg	665 kg	690 kg
Rozměry stroje (šířka x délka x výška)	85x175x105 cm	85x200x105 cm	85x225x105 cm	85x245x105 cm	85x200x105 cm	85x225x105 cm	85x245x105 cm	120x200x120 cm	120x225x120 cm	120x252x120 cm	120x200x120 cm	120x225x120 cm	120x252x120 cm

BS Ukazuje na pevný tiller
 BH Označuje hydraulickou převodovku
 4V Označuje 4stupňovou převodovku.



Produkt	Pracovní šířka
160 ORCHARD TYPE FIXED ROTARY TILLER	160
180 ORCHARD FIXED TYPE ROTARY TILLER	180
180 ORCHARD FIXED TYPE 4V ROTARY TILLER	180
180 ORCHARD HYDRAULIC SHIFT ROTARY TILLER	180
180 ORCHARD HYDRAULIC SHIFT 4V ROTARY TILLER	180
210 ORCHARD FIXED TYPE ROTARY TILLER	210
210 ORCHARD FIXED TYPE 4V ROTARY TILLER	210
210 ORCHARD HYDRAULIC SHIFT ROTARY TILLER	210
210 ORCHARDHYDRAULIC SHIFT 4V ROTARY TILLER	210
240 ORCHARD FIXED TYPE ROTARY TILLER	240
240 ORCHARD FIXED TYPE 4V ROTARY TILLER	240
240 ORCHARD HYDRAULIC SHIFT ROTARY TILLER	240
240 ORCHARD HYDRAULIC SHIFT 4V ROTARY TILLER	240

